

TSP-100 小型汎用圧力センサー

ご注文の際に、型番、仕様、レンジをご指定ください。

TSP100			T							
	①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩
型番				基本			特別説明			
① 型式	1	M12 コネクタ								
	2	シールドケーブル(長さ 1m)								
	3	Hirschmann コネクタ								
② 接続ネジ	1	R1/8								
	2	R1/4								
	3	G1/8A								
	4	G1/4A								
	5	1/8NPT								
	6	1/4NPT								
	X	特注品								
③ 接液部材質	T	SUS316								
④ 圧力レンジ (MPa)	1	-0.1~1.0	A	0~1.0						
	2	0~0.01	B	0~2.0						
	3	0~0.02	C	0~3.5						
	4	0~0.035	D	0~5.0						
	5	0~0.07	E	0~10						
	6	0~0.1	F	0~20						
	7	0~0.2	G	0~35						
	8	0~0.3	H	0~50						
	9	0~0.5	X	特注品						
⑤ 精度	1	±0.25%F.S.								
	2	±0.5%F.S.								
	3	±1.0%F.S.								
	X	特注品								
⑥ 電源/出力	1	5.0±0.5VDC	0.5~4.5VDC 3線							
	2	9~30VDC	0.5~4.5VDC 3線							
	3	9~30VDC	0~5VDC 3線							
	4	9~30VDC	1~5VDC 3線							
	5	9~30VDC	4~20mA 2線							
	6	12~30VDC	0~10VDC 3線							
⑦ ケーブル	0	コネクタ式、1mケーブル								
	1	ケーブル式、長さ指定								
① バルブ	0	付き								
	1	なし								
② 処理	0	なし								
	1	禁油処理								
	2	禁水処理								
③ 資料	3	禁油・禁水処理								
	0	なし								
	1	取説								

※ シールドケーブルの長さは 5mまで対応
できます、0.5m単位でご指定ください。